



Power Your Business to the next level
with Schneider Electric Power Solutions



<http://www.apc.com/in/en/>

Life Is On

APC[®]
by Schneider Electric

Back-UPS

APC Back-UPS range ideally provides battery backup with surge protection for wireless networks, computers, gaming consoles and other electronics in homes and small offices. The Back-UPS are designed to specifically to provide battery backup during power outages and protect critical data and electronic devices from unsafe voltage fluctuations arising from damaging surges and spikes.

APC Back-UPS models are available in both Tower and Floor forms and are equipped with a wide range of features, capacities and backup times to suit your specific applications and requirement. The APC by Schneider Electric's Back-UPS range is the ideal choice to protect your data and devices and keep you connected at all times.





Back-UPS	
BX600C-IN	
	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for single Home PC • Sockets - 3 Indian power sockets with surge protection • Front Panel - LED Display • Back up time <ul style="list-style-type: none"> Full Load (100%) 2.5 minutes Half Load (50%) 7.9 minutes Quarter Load (25%) 20 minutes • Warranty - Two years including battery



Back-UPS	
BE700Y-IND	
	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for single Multimedia PC/ Workstation PC/ Gaming PC/ Desktop • Sockets - 3 Indian power sockets with surge protection & 1 only surge protection socket • Front Panel - LED Display • Power Chute Software - Easy-to-use, safe system shutdown software with power and energy management features for home computers and battery backups • Backup time <ul style="list-style-type: none"> Full Load (100%) 3.5 minutes Half Load (50%) 11.9 minutes Quarter Load (25%) 28 minutes • Warranty - Two years including battery



Back-UPS	
BE800-IND	
	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for two PC Desktops • Sockets - 3 Indian power sockets with surge protection & 1 only surge protection socket • Front Panel - LED Display • Back up time <ul style="list-style-type: none"> Full Load (100%) 3.5 minutes Half Load (50%) 11.9 minutes Quarter Load (25 %) 28 minutes • Warranty - Two years including battery





Back-UPS	
BX1100C-IN	
	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for three PC Desktops (PC -120 Watts approx) & one Inkjet Printer • Sockets - 3 Indian power sockets with surge protection & 2 only surge protection sockets • Front Panel - LED Display • Back up time Full Load (100%) 3.5 minutes Half Load (50%) 14.1 minutes Quarter Load (25%) 35 minutes • Warranty - One year including battery



Back-UPS Pro	
BR1000G-IN	
	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for four PC Desktops (PC -120 Watts approx) & one Inkjet Printer • Sockets - 4 Indian power sockets with surge protection & 2 only surge protection sockets • Front Panel - LCD Display • Power Chute Software - Easy-to-use, safe system shutdown software with power and energy management features for home computers and battery backups • Back up time Full Load (100%) 6.4 minutes Half Load (50%) 18.5 minutes Quarter Load (25%) 39.9 minutes • Warranty - Two years including battery Optional Battery Pack





Product Family	Back-UPS
Model	BR1500G-IN
Description	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Application - for six PC Desktops (PC -120 Watts approx) & one Inkjet Printer • Sockets - 4 Indian power sockets with surge protection & 2 only surge protection sockets • Front Panel - LCD Display • Power Chute Software - Easy-to-use, safe system shutdown software with power and energy management features for home computers and battery backups • Back up time Full Load (100%) 2.6 minutes Half Load (50%) 9.8 minutes Quarter Load (25%) 25.3 minutes • Warranty -Two years including battery Optional Battery Pack



Product Family	Accessories
Model	BR24BPG-IN
Description	Back-UPS Pro External Battery Pack 24V



Product Family	Back-UPS
Model	BX1000UXI
Description	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Efficiency - 92% • Application - for PC & Mixed Load • Sockets - 4 Indian power sockets • Front Panel - LED Display • Back up time - External Battery recommended upto 200AH • Warranty - Two Years including Battery





Product Family	Back-UPS
Model	BX2000UXI
Description	<ul style="list-style-type: none"> • Back-UPS - Line Interactive Technology • Efficiency - 92% • Application - for PC & Mixed load • Sockets - Hard wiring • Front Panel - LED Display • Back up time - External Battery recommended upto 200AH • Warranty - Two years including Battery



Smart UPS - Online

APC Smart-UPS Online range provides high density, true double conversion online power protection for servers, voice & data networks, medical labs and light industrial applications. The Smart-UPS Online models are ideally suitable for business critical systems that require long hour duration runtimes and work in a harsh environment. The Smart-UPS Online models are equipped with state of the art Power Chute management software to ensure additional safety for network operating systems during power shutdowns and voltage fluctuations.

These models are available in both Rack and Tower convertible forms and are capable of supporting loads of 1 – 20 KVA. The recent 15 & 20 KVA models are ideally capable of supporting power hungry blade servers and heavily loaded equipment racks. All models above 6KVA are equipped with an integrated Network Management Card to facilitate remote management. The APC by Schneider Electric's Smart-UPS Online family offer a range of safety features such as internal bypass, input power factor correction and much more to ensure your critical data and equipments are protected from crippling power outages and voltage fluctuations.





Product Family	
Model	
Description	<ul style="list-style-type: none"> • Smart-UPS - Double Conversion Online Technology • Efficiency - 90% • Application - for PC & Mixed Load • Sockets- India 3 pin 6A • LED Status Display - with On line: On battery: Replace Battery and Overload indicators • Battery Type - Maintenance Free Sealed Lead - Acid Battery with suspended electrolyte: Leakproof • Warranty - 2 years repair or replace



Product Family	
Model	
Description	<ul style="list-style-type: none"> • Smart-UPS - Double Conversion Online Technology • Efficiency - 90% • Application - for PC & Mixed Load • Sockets - India 3 pin 6A • LED Status Display - With Load and Battery Bar-graphs and On Line : On Battery : Replace Battery and Overload Indicators • Battery Type - No internal battery - Uses external battery system • Warranty - 2 years repair or replace





Product Family	Smart-UPS - Online - SRC
Model	SRC2KUXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Online High Density Double Conversion Technology • Application - for Server/ Voice & Data/ Network/ MedicalLabs & Light Industrial • Applications- Harsh environment • Maximum Load Factor - 1600 Watts • Efficiency - 92.0% (at 100% load) • Crest Factor - 3:1 • Sockets -2 IEC 320 C13 and 1 Hard Wire 3-wire (PN+G) (international PC connectors) • Front Panel - LED+LCD Display • Power Chute Software- Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, External batteries - Optional depending on required run time • Built in Automatic Bypass • Warranty - Two years





Product Family	Smart-UPS - Online - SRC
Model	SRC3KUXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Online High Density Double Conversion Technology • Application - for Server/ Voice & Data/ Network/ Medical Labs & Light Industrial Applications-Harsh environment • Maximum Load Factor - 2400 Watts • Efficiency - 92.0% (at 100% load) • Crest Factor - 3:1 • Sockets - 2 IEC 320 C13 and hard wiring (international PC connectors) • Front Panel - LED+LCD Display • Power Chute Software - Business Edition 5 Nodes - v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • External Batteries - Optional depending on required run time • Built in Automatic Bypass • Warranty - Two years





Product Family	Smart-UPS - Online - SRC
Model	SRC5KUXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Online High Density Double Conversion Technology • Application - for Server/ Voice & Data/ Network/ Medical Labs & Light Industrial Applications - Harsh environment • Maximum Load Factor- 4500 Watts • Efficiency - 94.0% (at 100% load) • Crest Factor- 3:1 • Sockets - 1 Hard Wire 3-wire (PN+G) (international PC connectors) • Front Panel - LED+LCD Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • External Batteries - Optional depending on required run time • Built in Automatic Bypass • Warranty -Two years



Product Family	Smart-UPS - Online - SRC
Model	SRCE6KUXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Online High Density Double Conversion Technology • Application - for Server/ Voice & Data/ Network/ Medical Labs & Light Industrial Applications - Harsh environment • Maximum Load Factor - 5400 Watts • Efficiency - 94.0% (at 100% load) • Crest Factor- 3:1 • Sockets- 1 Hard Wire 3-wire (PN+G) (international PC connectors) • Front Panel - LED+LCD Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • External Batteries - Optional depending on required run time • Built in Automatic Bypass • Warranty - Two years





Product Family	Smart-UPS - Online - SRC
Model	SRC10KUXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Online High Density Double Conversion Technology • Application - for Server/ Voice & Data/ Network/ Medical Labs & Light Industrial Applications -Harsh environment • Maximum Load Factor- 9000 Watts • Efficiency - >94.0% (at 100% load) • Crest Factor - 3:1 • Sockets -1 Hard Wire 3-wire (HN+G) (international PC connectors) • Front Panel - LED+LCD Display • SNMP Card - Optional • External Batteries - Optional depending on required run time • Built in Automatic Bypass • Warranty -Two years



Smart UPS - Line Interactive

APC Smart-UPS Line Interactive award winning range of UPS are designed to handle mixed load applications in small and medium businesses and support servers, storage, networking and point of sale (POS) equipment. Smart-UPS Line Interactive models provide greater reliability and highly efficient clean network grade power at low, medium and high load levels that ideally suit modern

multi-core or virtualized servers with varying load consumption patterns. Smart-UPS Line Interactive models are equipped with LED displays, extended range automatic voltage regulation (AVR) and pure sine wave output on battery. The Smart Slot Interface provision enables installation of optional accessory cards to facilitate easier management and functionality.

The Smart-UPS Line Interactive models are available in Tower, Rack Mount, Rack/Tower convertible form factors with the option to add external batteries to extend run times especially for converged voice and data networks. Rack mounted Smart-UPS are ideal for powering blade or density optimized servers in a distributed power protection environment as primary protection. The Smart-UPS SULI range is an economical entry level option for small and medium businesses that ideally provides protection for switches, networking devices and POS devices.





Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA750I-IN
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Sine Wave Technology • Application - Low end servers/ PC's / LCD/ LED TV's/ Home Theaters Network/ ATM's/ Medical Equipment etc. • Efficiency - 96.3% (at 100% load) • Sockets - 6 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • Battery - In built • Back up time Full Load (100%) 3.4 minutes Half Load (50%) 12.5 minutes Quarter Load (25%) 28.1 minutes • Warranty - Two years including battery



Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA1000I-IN
Description	<ul style="list-style-type: none"> • Smart-UPS - line Interactive Sine Wave Technology • Application - Low end Servers/ PC's/ LCD/ LED TV's/ Home Theaters Network/ ATM's/ Medical Equipment etc • Efficiency - 96.3% (at 100% load) • Sockets - 6 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V,Red Hat Enterprise, Linux, VMware, Windows 2003, • Battery - In built • Back up time Full Load (100%) 6.1 minutes Half Load (50%) 20.0 minutes Quarter Load (25%) 60.1 minutes • Warranty -Two years including battery





Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA1500I-IN
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Sine Wave Technology • Application - Low end Servers/ PC's/ LCD/ LED TV's/ Home Theaters Network /ATM's/ Medical Equipment etc • Efficiency - 96.3% (at 100% load) • Sockets - 8 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • Battery - In built • Back up time <ul style="list-style-type: none"> Full Load (100%) 6.7 minutes Half Load (50%) 23.1 minutes Quarter Load (25%) 64.4 minutes • Warranty - Two years including battery



Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA2200I-IN
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Sine Wave Technology • Application - Low end Servers/ PC's/ LCD/ LED TV's/ Home Theaters Network/ ATM's/ Medical Equipment etc • Efficiency - 96.3% (at 100% load) • Sockets - 8 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • Battery - In built • Back up time <ul style="list-style-type: none"> Full Load (100%) 6.8 minutes Half Load (50%) 24.8 minutes Quarter Load (25% Watts) 69.6 minutes • Warranty - Two years including battery





Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA3000I-IN
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Sine Wave Technology • Application - Low end Servers/ PC's/ LCD/ LED TV's/ Home Theaters Network/ ATM's/ Medical Equipment etc • Efficiency - 96.3% (at 100% load) • Sockets - 8 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes-v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • Battery - In built • Back up time Full Load (100% Watts) 5.5 minutes Half Load (50%) 13.6 minutes Quarter Load (25%) 44.3 minutes • Warranty - Two years including battery



Smart UPS - Line Interactive - Extended Time



Product Family	Smart UPS - Line Interactive - Extended Time
Model	SUA1000UXI
Description	<ul style="list-style-type: none">• APC Smart-UPS XL 1000VA USB & Serial 230V• Application - for Servers, Point-of-Sale, Routers, Switches, Hubs and other Network Devices.• Battery - None Intelligent efficient network power protection from entry level to scalable runtime.



Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA2200UXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Technology with Pure Sine Wave Output • Application - Low end servers/ PC's/ LCD/ LED TV's/ Home Theaters/ Network/ ATM's/ Medical Equipment etc • Maximum Load Factor - 1980 Watts • Efficiency - 96.3% (at 100% load) • Sockets - 8 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes- v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • External Batteries - Optional depending on required run time • Warranty - Two years



Product Family	Smart-UPS - Line Interactive - (SULI)
Model	SUA3000UXI
Description	<ul style="list-style-type: none"> • Smart-UPS - Line Interactive Sine Wave Technology • Application - Low end Servers/ PC's/ LCD/ LED TV's/ Home Theaters/ Network/ ATM's/ Medical Equipment etc • Maximum Load Factor - 2700 Watts • Efficiency - 96.3% (at 100% load) • Sockets - 8 IEC 320 C13 (international PC connectors) & 2 IEC jumpers • Front Panel - LED Display • Power Chute Software - Business Edition 5 Nodes- v9.1.1 for Windows Hyper-V, Red Hat Enterprise, Linux, VMware, Windows 2003, • External Batteries - Optional depending on required run time • Warranty - Two years



Easy UPS Online

APC Easy UPS Online range is designed to specifically cater to power requirements of small and medium IT businesses that operate in harsh unreliable power conditions. APC Easy UPS range is feature rich and provides consistently clean, safe and reliable power at critical times to ensure power disruptions don't impact workflow and profitability.

The versatile Easy UPS range measures up to international bench marks in terms of quality and safety. The aesthetic design, build quality and the ability to handle a wide voltage range and deliver clean power in a harsh power environment is what sets it apart from other products.





Rail kit to be order separately - SRVRK1

Product Family	APC-Easy UPS 1Ph Online
Model	SRV2KL-IN
Description	<ul style="list-style-type: none"> • Double Conversion Online Sine Wave Output • Power Capacity - 1600W / 2000VA • Nominal Output Voltage 220/230/240VAC • Output Frequency Range - 60Hz or 50Hz +/- 0.1 Hz • Output Connections (4) 5-Pin Socket • Input Voltage Range - 110-300@ 60% Load • Input Frequency Range - 40Hz - 70Hz • Input Connection - IEC C14 • Battery Type - 12V / 9AH X 4 • Typical Recharge Time 4 Hours to Recover to 90% Capacity • Half Load Run Time - 10 Min • Full Load Run Time - 3 Min • DB-9 RS-232 Supports Windows 2000/2003/XP/Vista/2008/7/8 Linux, Unix & MAC • Multi-Function LCD Status Control Panel • Intelligent Slot - Mini Slot • Surge Energy Rating 600Joules



Rail kit to be order separately - SRVRK1

Product Family	APC-Easy UPS 1Ph Online
Model	SRV3KL-IN
Description	<ul style="list-style-type: none"> • Double Conversion Online Sine Wave Output • Power Capacity - 2400W / 3000VA • Nominal Output Voltage 220/230/240VAC • Output Frequency Range 60Hz or 50Hz +/- 0.1 Hz • Output Connections (4) 5-Pin Socket • Input Voltage Range 110-300@ 60% Load • Input Frequency Range 40Hz - 70Hz • Input Connection IEC C20 • Battery Type 12V / 9AH X 6 • Typical Recharge Time 4 Hours to Recover to 90% Capacity • Half Load Run Time 11 Min • Full Load Run Time 3 Min • DB-9 RS-232 Supports Windows 2000/2003/XP/Vista/2008/7/8 Linux, Unix & MAC • Multi-Function LCD Status Control Panel • Intelligent Slot - Mini Slot • Surge Energy Rating 600Joules



Product Family	APC-Easy UPS 1Ph Online
Model	SRV5KRIL-IN
Description	<ul style="list-style-type: none"> • Double Conversion Online Sine Wave Output • Power Capacity - 5000W / 5000VA • Nominal Output Voltage 220/230/240VAC • Output Frequency Range 60Hz or 50Hz +/- 0.1 Hz • Output Connections Terminal Block • Input Voltage Range 110-300@ 60% Load • Input Frequency Range 40Hz - 70Hz • Input Connection Terminal Block • Battery Type 12V / 7AH X 20 • Typical Recharge Time 4 Hours to Recover to 90% Capacity • Half Load Run Time 20.5 Min • Full Load Run Time 8 Min • DB-9 RS-232 Supports Windows 2000/ 2003/XP/Vista/2008/7/8 Linux, Unix & MAC • Multi-Function LCD Status Control Panel Intelligent Slot - Mini Slot • Surge Energy Rating 600Joules



Product Family	APC-Easy UPS 1Ph Online
Model	SRV6KRIL-IN
Description	<ul style="list-style-type: none"> • Double Conversion Online Sine Wave Output • Power Capacity - 6000W / 6000VA • Nominal Output Voltage 220/230/240VAC • Output Frequency Range 60Hz or 50Hz +/- 0.1 Hz • Output Connections Terminal Block • Input Voltage Range 110-300@ 60% Load • Input Frequency Range 40Hz - 70Hz • Input Connection Terminal Block • Battery Type 12V / 9AH X 20 • Typical Recharge Time 4 Hours to Recover to 90% Capacity • Half Load Run Time 16.5 Min • Full Load Run Time 6 Min • DB-9 RS-232 Supports Windows 2000/ 2003/XP/Vista/2008/7/8 Linux, Unix & MAC • Multi-Function LCD Status Control Panel Intelligent Slot - Mini Slot • Surge Energy Rating 600Joules



Product Family	APC-Easy UPS 1Ph Online
Model	E3SUPS15KH
Description	<ul style="list-style-type: none"> • Double Conversion Mode (upto 96%) • ECO Mode (99% Efficiency) • Common Battery under 1+1mode • Parallel upto 4 • Conformal Coating on PCBA • In-built Replaceable Dust Filter • Operating Temperature Up To 40C • Output Power Capacity - 15.0 KW / 15.0 kVA • Output Voltage THD - < 3% linear load • Overload Operation - 150% for 1 min 125% for 10 min • Bypass - Built-in Maintenance Bypass • Maximum Input Current - 28 A • Input Frequency - 45 - 65 Hz • Input Total Harmonic Distortion - Less than 3% for full load • Interface Port(s) - E3S_Parallel, • E3S_TempSensor • 20% Power as Charging Capacity • Mimic Panel Multi Language LCD Display (EPO Inbuilt) • RoHS Compliance



Product Family	APC-Easy UPS 3Ph Online
Model	E3SUPS20KH
Description	<ul style="list-style-type: none"> • Double Conversion Mode (upto 96%) • ECO Mode (99% Efficiency) • Common Battery under 1+1mode • Parallel upto 4 • Conformal Coating on PCBA • In-built Replaceable Dust Filter • Operating Temperature Up To 40C • Output Power Capacity - 20.0 KW / 20.0 kVA • Output Voltage THD - < 3% linear load • Overload Operation - 150% for 1 min 125% for 10 min • Bypass - Built-in Maintenance Bypass • Maximum Input Current - 37 A • Input Frequency - 45 - 65 Hz • Input Total Harmonic Distortion - Less than 3% for full load • Interface Port(s) - E3S_Parallel, • E3S_TempSensor • 20% Power as Charging Capacity • Mimic Panel Multi Language LCD Display (EPO Inbuilt) • RoHS Compliance



Product Family	APC-Easy UPS 3Ph Online
Model	E3SUPS15K3I
Description	<ul style="list-style-type: none"> • Double Conversion Mode (upto 96%) • ECO Mode (99% Efficiency) • Common Battery under 1+1mode • Parallel upto 4 • Conformal Coating on PCBA • In-built Replaceable Dust Filter • Operating Temperature Up To 40C • Output Power Capacity - 15.0 KW / 15.0 kVA • Output Voltage THD - < 3% linear load • Overload Operation - 150% for 1 min 125% for 10 min • Bypass - Built-in Maintenance Bypass • Maximum Input Current - 55 A • Input Frequency - 45 - 65 Hz • Input Total Harmonic Distortion - Less than 3% for full load Interface Port(s) - E3S_Parallel, • E3S_TempSensor • 20% Power as Charging Capacity • Mimic Panel Multi Language LCD Display (EPO Inbuilt) • RoHS Compliance



Product Family	APC-Easy UPS 3Ph Online
Model	E3SUPS20K3I
Description	<ul style="list-style-type: none"> • Double Conversion Mode (upto 96%) • ECO Mode (99% Efficiency) • Common Battery under 1+1mode • Parallel upto 4 • Conformal Coating on PCBA • In-built Replaceable Dust Filter • Operating Temperature Up To 40C • Output Power Capacity - 20.0 KW / 20.0 kVA • Output Voltage THD - < 3% linear load • Overload Operation - 150% for 1 min 125% for 10 min • Bypass - Built-in Maintenance Bypass • Maximum Input Current - 37 A • Input Frequency - 45 - 65 Hz • Input Total Harmonic Distortion - Less than 3% for full load Interface Port(s) - E3S_Parallel, • E3S_TempSensor • 20% Power as Charging Capacity • Mimic Panel Multi Language LCD Display (EPO Inbuilt) • RoHS Compliance

Accessories



Product Family	Accessories
Model	SURTRK2
Description	APC Smart-UPS RT 19" Rail Kit for Smart-UPS RT 3/5/7.5/10KVA



Product Family	Accessories
Model	SURTRK5
Description	APC Smart-UPS RT 19" Rail Kit for SRC 3 KVA



Product Family	Accessories
Model	SRC96XLBP
Description	APC Smart-UPS RC 96V Battery Pack



Product Family	Accessories
Model	SRC96XLBP2S
Description	APC Smart-UPS RC 96V Battery Pack with 1 Battery String





Product Family	Accessories
Model	SURT192XLBP
Description	APC Smart-UPS RT 192V Battery Pack

Product Family	Accessories
Model	AP9630
Description	UPS Network Management Card 2 Remote monitoring and control of an individual UPS by connecting it directly to the network.

Product Family	Accessories
Model	AP9631
Description	UPS Network Management Card 2 with Environmental Monitoring Remote monitoring and control of an individual UPS by connecting it directly to the network.

Product Family	Accessories
Model	AP4423
Description	RACK ATS, 230V, 16A, C20 IN, (8) C13 (1) C19 OUT Provides redundant rack mount power to single-corded equipment.

Product Family	Accessories
Model	AP4424
Description	Rack ATS, 230V, 32A, IEC 309 in, (16) C13 (2) C19 out Provides redundant rack mount power to single-corded equipment.





Product Family	Accessories
Model	SRCPK0506
Description	APC Smart-UPS RC Paralleling Kit for 5 & 6 KVA



Product Family	Accessories
Model	AP8858EU3
Description	Rack PDU 2G, Metered, ZeroU, 16A, 230V, (18) C13 & (2) C19, IEC309 Cord APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection



Product Family	Accessories
Model	SRC192XLBP-IN
Description	APC Smart-UPS RC 192V Battery Pack



Product Family	Accessories
Model	SRCPK0203
Description	APC Smart-UPS Paralleling Kit for 2 and 3KVA, India Specific High density, double-conversion on-line power protection with scalable runtime





Product Family	Accessories
Model	E3SOPT001
Description	Easy UPS 3 Series Network Card



Product Family	Accessories
Model	E3SOPT002
Description	Easy UPS 3S Parallel Kit

Product Family	Accessories
Model	E3SOPT003
Description	Temperature sensor Kit for external battery system

