



## Harmony Relays

Electromechanical, Timer and control Relays

Enhance **operational efficiency** and **optimize equipment availability** with our widest range of relays. Harmony relays are designed, manufactured, and tested to meet your needs for both wired logic functions and PLC Interfaces.

[se.com/in](https://se.com/in)



- **Wide choice:** 1C/O 10 A – 2C/O 5 A, 6 VDC – 230 VAC, multifunctional features
- **Robust installation:** fast-on pin terminal
- **Easy to use:** optional status indication and test function
- **Safe to perform:** feasibility to add protection modules (diode, diode + LED, RC circuit, or varistor + LED)
- **Space saving:** only 16 mm socket for 2C/O

## RXG Interface Relays NEW

Description	Relay	Control Circuit Voltage (V)	Reference	Unit MRP [€]	
<b>1CO 6 Pin Relay Standard cover lockable test button</b>					
Without LED indicator	1 CO - 10 A	24V	DC	RXG11BD	558
	1 CO - 10 A	24V	AC	RXG11B7	714
	1 CO - 10 A	120V	AC	RXG11F7	735
	1 CO - 10 A	230V	AC	RXG11P7	694
<b>1CO 6 Pin Relay Standard cover lockable test button</b>					
With LED indicator	1 CO - 10 A	24V	DC	RXG12BD	629
	1 CO - 10 A	24V	AC	RXG12B7	755
	1 CO - 10 A	120V	AC	RXG12F7	755
	1 CO - 10 A	230V	AC	RXG12P7	755
<b>1CO 6 Pin Relay without locable test button</b>					
With LED indicator	1 CO - 10 A	24V	DC	RXG13BD	586
	1 CO - 10 A	120V	AC	RXG13F7	803
	1 CO - 10 A	230V	AC	RXG13P7	739
<b>1CO 6 Pin Relay without locable test button</b>					
Without LED indicator	1 CO - 10 A	12V	DC	RXG15JD	517
	1 CO - 10 A	24V	DC	RXG15BD	528
	1 CO - 10 A	230V	AC	RXG15P7	629
<b>2CO 8 Pin Relay Standard cover lockable test button</b>					
Without LED indicator	2 CO - 5 A	12V	DC	RXG21JD	639
	2 CO - 5 A	24V	DC	RXG21BD	628
	2 CO - 5 A	120V	AC	RXG21F7	762
	2 CO - 5 A	220V	AC	RXG21M7	820
	2 CO - 5 A	230V	AC	RXG21P7	748
<b>2CO 8 Pin Relay Standard cover lockable test button</b>					
With LED indicator	2 CO - 5 A	24V	DC	RXG22BD	699
	2 CO - 5 A	48V	DC	RXG22ED	724
	2 CO - 5 A	24V	AC	RXG22B7	840
	2 CO - 5 A	120V	AC	RXG22F7	840
	2 CO - 5 A	220V	AC	RXG22M7	824
	2 CO - 5 A	230V	AC	RXG22P7	840
<b>2CO 8 Pin Relay Standard cover without lockable test button</b>					
With LED indicator	2 CO - 5 A	24V	DC	RXG23BD	655
	2 CO - 5 A	24V	AC	RXG23B7	793
	2 CO - 5 A	120V	AC	RXG23F7	793
	2 CO - 5 A	220V	AC	RXG23M7	793
	2 CO - 5 A	230V	AC	RXG23P7	807
<b>2CO 8 Pin Relay Standard cover without lockable test button</b>					
Without LED indicator	2 CO - 5 A	12V	DC	RXG25JD	557
	2 CO - 5 A	24V	DC	RXG25BD	567
	2 CO - 5 A	220V	AC	RXG25M7	735
	2 CO - 5 A	230V	AC	RXG25P7	695

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 17<sup>th</sup>, 2024



- 5A relay with 2C/O contacts or 3A relay with 4 C/O contacts
- Mechanical indicator with transparent cover
- Power On\* LED for readiness
- Socket for both DIN-rail and panel mounting
- Eco-design with ROHS, CE, GOST

## RXM Miniature Relays

Description	Relay	Control Circuit Voltage (V)		Reference	Unit MRP [₹]
<b>2 CO 8 Pin relays Without lockable test button</b>					
Without LED indicator	2 CO - 5 A	24V	DC	RXM2LB1BD	423
	2 CO - 5 A	24V	AC	RXM2LB1B7	442
	2 CO - 5 A	120V	AC	RXM2LB1F7	442
	2 CO - 5 A	230V	AC	RXM2LB1P7	433
With LED indicator	2 CO - 5 A	24V	DC	RXM2LB2BD	455
	2 CO - 5 A	48V	DC	RXM2LB2ED	488
	2 CO - 5 A	24V	AC	RXM2LB2B7	488
	2 CO - 5 A	120V	AC	RXM2LB2F7	488
	2 CO - 5 A	230V	AC	RXM2LB2P7	455
<b>4 CO 14 Pin relays Without lockable test button</b>					
Without LED indicator	4 CO - 3 A	12V	DC	RXM4LB1JD	598
	4 CO - 3 A	24V	DC	RXM4LB1BD	488
	4 CO - 3 A	24V	AC	RXM4LB1B7	536
	4 CO - 3 A	230V	AC	RXM4LB1P7	488
With LED indicator	4 CO - 3 A	12V	DC	RXM4LB2JD	550
	4 CO - 3 A	24V	DC	RXM4LB2BD	515
	4 CO - 3 A	48V	DC	RXM4LB2ED	550
	4 CO - 3 A	24V	AC	RXM4LB2B7	550
	4 CO - 3 A	120V	AC	RXM4LB2F7	550
	4 CO - 3 A	230V	AC	RXM4LB2P7	515

Description	Type	Reference	Unit MRP [₹]
<b>Sockets</b>			
Mixed,screw clamp term, for RXM2L range	Socket	RXZE1M2C	214
Mixed,screw clamp term, for RXM4L range	Socket	RXZE1M4C	273
Metal clamp for RXZE1M2C	Accessory	RXZ420	51

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 17<sup>th</sup>, 2024

**RXM\*NB Miniature Relays**

Description	Relay	Control Circuit Voltage (V)		Reference	Unit MRP [₹]
<b>Miniature Relays without Lockable Test-Button</b>					
With LED indicators	2 CO - 10 A	24V	DC	RXM2NB3BD	492
	2 CO - 10 A	120V	DC	RXM2NB3FD	545
	2 CO - 10 A	220V	DC	RXM2NB3MD	696
	2 CO - 10 A	230V	AC	RXM2NB3P7	545
	2 CO - 10 A	24V	DC	RXM4NB3BD	608
	2 CO - 10 A	120V	AC	RXM4NB3F7	619
	2 CO - 10 A	230V	AC	RXM4NB3P7	579

Description	Connection	Relay Type	Reference	Unit MRP [₹]
<b>Sockets for RXMNB Relays</b>				
Mixed	Screw Clamp connector	RXN2N	RXZE2M2N	229
Mixed	Screw Clamp connector	RXN4N	RXZE2M4N	261

**RPM Power Relay**

Description	Relay	Control Circuit Voltage (V)		Reference	Unit MRP [₹]
<b>Power Relay</b>					
With LED Indicators	1 CO - 15 A	24V	DC	RPM12BD	873
	2 CO - 15 A	24 V	DC	RPM22BD	1158
	2 CO - 15 A	120V	AC	RPM22F7	1556
	2 CO - 15 A	230V	AC	RPM22P7	1305
	3 CO - 15 A	24V	DC	RPM32BD	1474
	3 CO - 15 A	230V	AC	RPM32P7	1503
	4 CO - 15 A	24V	DC	RPM42BD	1417
	4 CO - 15 A	48V	DC	RPM42ED	1512
	4 CO - 15 A	110V	DC	RPM42FD	1536
	4 CO - 15 A	24V	AC	RPM42B7	1401
	4 CO - 15 A	48V	AC	RPM42E7	1465
	4 CO - 15 A	110V	AC	RPM42F7	1574
	4 CO - 15 A	230V	AC	RPM42P7	1392

Description	Connection	Relay Type	Reference	Unit MRP [₹]
<b>Sockets</b>				
Mixed	Screw Clamp connector	RPM1	RPZF1	562
Mixed	Screw Clamp connector	RPM2	RPZF2	564
Mixed	Screw Clamp connector	RPM3	RPZF3	996
Mixed	Screw Clamp connector	RPM4	RPZF4	962
<b>Clips And Legends</b>				
Metal maintaining clamp - for relay socket RPZF1			RPZR235	151

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 17<sup>th</sup>, 2024



- High-performance EMR Relays to ensure machine and system availability.
- Flexible choices with different contact numbers, current, and control coil voltages.
- 12A relay with 2C/O contacts or 6A relay with 4 C/O contacts
- One step lockable test button
- Mechanical indicator for contact status
- Power on" LED for readines

## RXM Miniature Relays

Description	Relay	Control Circuit Voltage (V)		Reference	Unit MRP [₹]
<b>2CO 8 Pin Relay Standard cover lockable test button</b>					
Without LED indicator	2 CO - 12 A	12V	DC	RXM2AB1JD	659
	2 CO - 12 A	24V	DC	RXM2AB1BD	634
	2 CO - 12 A	48V	DC	RXM2AB1ED	696
	2 CO - 12 A	110V	DC	RXM2AB1FD	665
	2 CO - 12 A	24V	AC	RXM2AB1B7	659
	2 CO - 12 A	48V	AC	RXM2AB1E7	659
	2 CO - 12 A	120V	AC	RXM2AB1F7	659
	2 CO - 12 A	230V	AC	RXM2AB1P7	634
<b>2CO 8 Pin Relay Standard cover lockable test button</b>					
With LED indicator	2 CO - 12 A	12V	DC	RXM2AB2JD	688
	2 CO - 12 A	24V	DC	RXM2AB2BD	659
	2 CO - 12 A	48V	DC	RXM2AB2ED	726
	2 CO - 12 A	110V	DC	RXM2AB2FD	675
	2 CO - 12 A	24V	AC	RXM2AB2B7	683
	2 CO - 12 A	48V	AC	RXM2AB2E7	675
	2 CO - 12 A	120V	AC	RXM2AB2F7	688
	2 CO - 12 A	230V	AC	RXM2AB2P7	659
<b>3CO 11 Pin Relay Standard cover with lockable test button</b>					
With LED indicator	3 CO - 10 A	12V	DC	RXM3AB1JD	881
	3 CO - 10 A	24V	DC	RXM3AB1BD	880
	3 CO - 10 A	24V	AC	RXM3AB1B7	981
	3 CO - 10 A	120V	AC	RXM3AB1F7	906
	3 CO - 10 A	230V	AC	RXM3AB1P7	906
<b>3 CO 11 Pin Relay Standard cover with lockable test button</b>					
Without LED indicator	3 CO - 10 A	24V	DC	RXM3AB2BD	842
	3 CO - 10 A	48V	DC	RXM3AB2ED	1036
	3 CO - 10 A	110V	DC	RXM3AB2FD	975
	3 CO - 10 A	24V	AC	RXM3AB2B7	916
	3 CO - 10 A	120V	AC	RXM3AB2F7	881
	3 CO - 10 A	230V	AC	RXM3AB2P7	881
<b>4CO 14 Pin Relay Standard cover with lockable test button</b>					
With LED indicator	4 CO - 6 A	12V	DC	RXM4AB1JD	789
	4 CO - 6 A	24V	DC	RXM4AB1BD	789
	4 CO - 6 A	48V	DC	RXM4AB1ED	879
	4 CO - 6 A	110V	DC	RXM4AB1FD	879
	4 CO - 6 A	24V	AC	RXM4AB1B7	805
	4 CO - 6 A	48V	AC	RXM4AB1E7	827
	4 CO - 6 A	120V	AC	RXM4AB1F7	805
	4 CO - 6 A	230V	AC	RXM4AB1P7	805
	<b>4 CO 14 Pin Relay Standard cover with lockable test button</b>				
Without LED indicator	4 CO - 6 A	12V	DC	RXM4AB2JD	920
	4 CO - 6 A	24V	DC	RXM4AB2BD	874
	4 CO - 6 A	48V	DC	RXM4AB2ED	920
	4 CO - 6 A	110V	DC	RXM4AB2FD	920
	4 CO - 6 A	24V	AC	RXM4AB2B7	937
	4 CO - 6 A	48V	AC	RXM4AB2E7	937
	4 CO - 6 A	120V	AC	RXM4AB2F7	937
	4 CO - 6 A	230V	AC	RXM4AB2P7	891

Please contact Customer Care Center for Stockable and Non stockable status of references.

NORMAL STOCK ITEMS

W.E.F. January 17<sup>th</sup>, 2024

## RXM Miniature Relays

Description	Connection	Relay Type	Thermal Current (Ith)	Reference	Unit MRP [₹]
<b>Sockets</b>					
Mixed contact	Screw Clamp	RXM2* / RXM4*	10A	RXZE2M114	334
	Screw Connector	RXM2* / RXM4*	10A	RXZE2M114M	300
Separate	Screw Connector	RXM2*	12A	RXZE2S108M	348
	Screw Connector	RXM3*	10A	RXZE2S111M	385
	Screw Connector	RXM4*	10A	RXZE2S114M	411

Description	Voltage V	For use with	Reference	Unit MRP [₹]
<b>Sockets</b>				
Diode	6...250 V DC	All Sockets	RXM040W	157
RC Circuit	24..60 V AC	All Sockets	RXM041BN7	168
	110..240 V AC	All Sockets	RXM041FU7	168
RC Circuit	6..24 V AC/DC	All Sockets	RXM021RB	198
	24..60 V AC/DC	All Sockets	RXM021BN	198
	110..240 V AC/DC	All Sockets	RXM021FP	188